

HPP3耐磨板

Anti-Wear Plates

产品特性 Product Features

- 连续使用温度: -50℃ / +90℃
 - 适合干运行、免维护
 - 不同轴材料磨损很小
 - 较低的摩擦系数
 - 适用于软轴
 - 吸水性较低
- Continuous working temperature: -50/+90℃
 - Maintenance-free dry operation
 - Small wear off amount against various shaft materials
 - Lower friction
 - Suitable for soft shaft
 - Low water absorption



订购编码 Order PN

订购编码 Order PN:
HPP3-10-0600-0700

材料 Material
厚度 Thickness
宽度 Width
长度 Length

订购编码 OrderPN	厚度 Thickness [mm]	公差 Tolerance [mm]	宽度 Width [mm]	长度 Length L[mm]
HPP3-10-0600-L	10	+0.20/+0.90	600	100-1000
HPP3-15-0600-L	15	+0.30/+1.50	600	100-1000
HPP3-20-0600-L	20	+0.30/+1.50	600	100-1000
HPP3-25-0600-L	25	+0.30/+1.50	600	100-1000
HPP3-30-0600-L	30	+0.50/+2.50	600	100-1000

MB81耐磨板

Anti-Wear Plates

产品特性 Product Features

- 自润滑、免维护
 - 低摩擦、耐磨损
 - 抗冲击、低噪音
 - 极低吸水性
 - 耐低温 -196℃
- Maintenance-free, self-lubricated
 - Low friction, anti-wear
 - Impact resistance, low noise
 - Low water absorption
 - Very low temperature -196℃



订购编码 Order PN

订购编码 Order PN:
MB81-10-0600-0700

材料 Material
厚度 Thickness
宽度 Width
长度 Length

订购编码 OrderPN	厚度 Thickness [mm]	公差 Tolerance [mm]	宽度 Width [mm]	长度 Length L[mm]
MB81-10-0600-L	10	+0.20/+0.90	600	100-1000
MB81-15-0600-L	15	+0.30/+1.50	600	100-1000
MB81-20-0600-L	20	+0.30/+1.50	600	100-1000
MB81-25-0600-L	25	+0.30/+1.50	600	100-1000
MB81-30-0600-L	30	+0.50/+2.50	600	100-1000
MB81-35-0600-L	35	+0.50/+2.50	600	100-1000
MB81-40-0600-L	40	+0.50/+2.50	600	100-1000